

This is an Open Access document downloaded from ORCA, Cardiff University's institutional repository:<https://orca.cardiff.ac.uk/id/eprint/157478/>

This is the author's version of a work that was submitted to / accepted for publication.

Citation for final published version:

Anning, Kate L., Langley, Kate , Hobson, Christopher, De Sonneville, Leo and Van Goozen, Stephanie H.M. 2024. Inattention symptom severity and cognitive processes in children at risk of ADHD: The moderating role of separation anxiety. *Child Neuropsychology* 30 (2) , pp. 264-288. 10.1080/09297049.2023.2190964

Publishers page: <https://doi.org/10.1080/09297049.2023.2190964>

Please note:

Changes made as a result of publishing processes such as copy-editing, formatting and page numbers may not be reflected in this version. For the definitive version of this publication, please refer to the published source. You are advised to consult the publisher's version if you wish to cite this paper.

This version is being made available in accordance with publisher policies. See <http://orca.cf.ac.uk/policies.html> for usage policies. Copyright and moral rights for publications made available in ORCA are retained by the copyright holders.



Supplementary Information

<i>Table S1.....</i>	2
<i>SPSS Syntax Used for Dimensional Symptom Scores and Research Diagnoses</i>	3

Table S1.

Sensitivity analysis correlations with children with anxiety removed from the sample (n = 93)

	1	2	3	4	5	6	7	8	9	10	11
1. Age	--										
2. BPVS	.560**	--									
3. Inatt	.036	-.066	--								
4. Hyp-Imp	.002	-.109	.817**	--							
5. AWMA	-.142	.114	-.063	.090	--						
6. PSM	.227*	.181	-.263*	-.147	.189	--					
7. RI RT	-.232*	-.391**	.211*	.089	-.131	-.134	--				
8. RI % errors	-.257*	-.292**	.206*	.108	-.362**	-.269**	.489**	--			
9. RI Var	-.261*	-.332**	.330**	.256*	-.167	-.173	.579**	.390**	--		
10. VM	.081	-.032	.186	.087	-.224*	-.055	.310**	.463**	.125	--	
11. SA	-.191	-.129	.243*	.154	-.051	-.363**	.214*	.241*	.194	.536**	--
12. VM Var	-.232*	-.204	.233*	.155	-.157	-.287**	.380**	.399**	.299**	.589**	.830**

Note. * p < .05, ** p < .01. Inatt = inattention. Hyp-Imp = Hyperactivity-Impulsivity. AWMA = Automated Working Memory Assessment. PSM= Picture Sequence Memory. RI = Response Inhibition. RT = Response Time. Var = Variability. VM = Visuomotor control. VM Var = visuomotor control variability. SA=Sustained Attention.

SPSS Syntax Used for Dimensional Symptom Scores and Research Diagnoses

***ATTENTION DEFICIT HYPERACTIVITY DISORDER (ADHD) ***

**Overall diagnosis Conservative - adhdDiagnosis

***ADHD - INATTENTIVE

*ADHD-INATTENTIVE SYMPTOM SCORE (CONSERVATIVE) = inattSymptomScoreCon

***ADHD - HYPERACTIVE/IMPULSIVE

*ADHD-HYPERACTIVE/IMPULSIVE SYMPTOM SCORE (CONSERVATIVE) =
hypimpSymptomScoreCon

***ADHD - COMBINED

*ADHD-COMBINED SYMPTOM SCORE (CONSERVATIVE) = SymptomScoreCon /

compute mis_adhd = missing(p1j1).
execute.

*A) ADHD-INATTENTIVE CONSERVATIVE score - symptom count past 6 months.

*Those who do not pass the screening question will score 0 here.

*as conservative, item endorsed if score = 2 'a lot more than others'

*six (or more) of the following symptoms of inattention have persisted for at least 6 months

*to a degree that is maladaptive and inconsistent with developmental level:

```
compute inattConscore =0.  
if (mis_adhd eq 1) inattConscore = 99.  
mis val inattConscore (99).  
if (p1j4a = 2) inattConscore = inattConscore+1.  
if (p1j4b = 2) inattConscore = inattConscore+1.  
if (p1j4c = 2) inattConscore = inattConscore+1.  
if (p1j4d = 2) inattConscore = inattConscore+1.  
if (p1j4e = 2) inattConscore = inattConscore+1.  
if (p1j4f = 2) inattConscore = inattConscore+1.  
if (p1j4g = 2) inattConscore = inattConscore+1.  
if (p1j4h = 2) inattConscore = inattConscore+1.  
if (p1j4i = 2) inattConscore = inattConscore+1.  
execute.
```

```

compute inattentionCon = 0.
if (mis_adhd eq 1) inattentionCon = 99.
mis val inattentionCon (99).
IF (inattConscore >= 6) inattentionCon=1.
EXECUTE.
IF (inattConscore < 6) inattentionCon=0.
EXECUTE.

```

*A) ADHD-HYPERACTIVE/IMPULSIVE

```

compute hypimpConscore =0.
if (mis_adhd eq 1) hypimpConscore = 99.
mis val hypimpConscore (99).
if (p1j2a = 2) hypimpConscore = hypimpConscore+1.
if (p1j2b = 2) hypimpConscore = hypimpConscore+1.
if (p1j2c = 2) hypimpConscore = hypimpConscore+1.
if (p1j2d = 2) hypimpConscore = hypimpConscore+1.
if (p1j2e = 2) hypimpConscore = hypimpConscore+1.
if (p1j3a = 2) hypimpConscore = hypimpConscore+1.
if (p1j3b = 2) hypimpConscore = hypimpConscore+1.
if (p1j3c = 2) hypimpConscore = hypimpConscore+1.
if (p1j3d = 2) hypimpConscore = hypimpConscore+1.
execute.

```

```

compute hypimpCon = 0.
if (mis_adhd eq 1) hypimpCon = 99.
mis val hypimpCon (99).
IF (hypimpConscore >= 6) hypimpCon=1.
EXECUTE.
IF (hypimpConscore < 6) hypimpCon=0.
EXECUTE.

```

*B) Symptoms are present across mutliple settings

**INATTENTIVENSS

```

compute inattentionPervasiveness = 0.
if (mis_adhd eq 1) inattentionPervasiveness = 99.
mis val inattentionPervasiveness (99).
IF (p1j5b = 2) inattentionPervasiveness=1.
EXECUTE.

```

*B) HYPERACTIVITY/IMPULSIVE Symptoms are present across multiple settings

```
compute hypImpPervasiveness = 0.
if (mis_adhd eq 1) hypImpPervasiveness = 99.
mis val hypImpPervasiveness (99).
IF (p1j5a = 2 OR p1j5c = 2) hypImpPervasiveness=1.
EXECUTE.
```

*C) Clear evidence of clinically significant impairment in social, academic or occupational functioning

*CONSERVATIVE presence of impairment

```
compute adhdInterferenceCon = 0.
if (mis_adhd eq 1) adhdInterferenceCon = 99.
mis val adhdInterferenceCon (99).
if (p1j9a =3) adhdInterferenceCon = adhdInterferenceCon + 1.
if (p1j9b =3) adhdInterferenceCon = adhdInterferenceCon + 1.
if (p1j9c =3) adhdInterferenceCon = adhdInterferenceCon + 1.
if (p1j9d =3) adhdInterferenceCon = adhdInterferenceCon + 1.
execute.
```

```
compute adhdInterferenceConPresent = 0.
if (mis_adhd eq 1) adhdInterferenceConPresent = 99.
mis val adhdInterferenceConPresent (99).
if (adhdInterferenceCon >= 1) adhdInterferenceConPresent = 1.
execute.
```

* DIAGNOSIS - INATTENTIVE, presence of A, B and C

```
compute InattDiagCriteriaCon = 0.
if (mis_adhd eq 1) InattDiagCriteriaCon = 99.
mis val InattDiagCriteriaCon (99).
if (inattentionCon =1 AND inattentionPervasiveness = 1 AND adhdInterferenceConPresent)
InattDiagCriteriaCon = 1.
EXECUTE.
```

* DIAGNOSIS - HYP/IMPULSIVE, presence of A, B and C

```
compute HypImpDiagCriteriaCon = 0.
if (mis_adhd eq 1) HypImpDiagCriteriaCon = 99.
```

```

mis val HypImpDiagCriteriaCon (99).
if (hypimpCon =1 AND hypImpPervasiveness = 1 AND adhdInterferenceConPresent)
HypImpDiagCriteriaCon = 1.
EXECUTE.

```

*ADHD DIAGNOSIS

```

compute adhdDiagnosis = 0.
if (mis_adhd eq 1) adhdDiagnosis = 99.
mis val adhdDiagnosis (99).
if (InattDiagCriteriaCon = 1 AND HypImpDiagCriteriaCon = 0) adhdDiagnosis = 1.
if (InattDiagCriteriaCon = 0 AND HypImpDiagCriteriaCon = 1) adhdDiagnosis = 2.
if (InattDiagCriteriaCon = 1 AND HypImpDiagCriteriaCon = 1) adhdDiagnosis = 3.
EXECUTE.

```

*SYMPTOM SCORE

*Inatt

```

compute inattSymptomScoreCon = inattConscore.
if (mis_adhd eq 1) inattSymptomScoreCon = 99.
mis val inattSymptomScoreCon (99).
EXECUTE.

```

*Hyp

```

compute hypimpSymptomScoreCon = hypimpConscore.
if (mis_adhd eq 1) hypimpSymptomScoreCon = 99.
mis val hypimpSymptomScoreCon (99).
EXECUTE.

```

*SEPARATION ANXIETY DIAGNOSIS CONSERVATIVE = sepConDiag

*SEPARATION ANXIETY SYMPTOM SCORE (CONSERVATIVE) = sepSymptomScore

SEPARATION ANXIETY**.

*A) Three symptoms are required

```

compute mis_sep = missing(p1a2).
execute.

```

```

compute DAWBAsepAnxietyConservative = 0.
if (mis_sep eq 1) DAWBAsepAnxietyConservative =99.
mis val DAWBAsepAnxietyConservative (99).
if (p1a3a eq 2) DAWBAsepAnxietyConservative = DAWBAsepAnxietyConservative+1.
if (p1a3b eq 2) DAWBAsepAnxietyConservative = DAWBAsepAnxietyConservative+1.
if (p1a3c eq 2) DAWBAsepAnxietyConservative = DAWBAsepAnxietyConservative+1.
if (p1a3d eq 2) DAWBAsepAnxietyConservative = DAWBAsepAnxietyConservative+1.
if (p1a3e eq 2) DAWBAsepAnxietyConservative = DAWBAsepAnxietyConservative+1.
if (p1a3f eq 2) DAWBAsepAnxietyConservative = DAWBAsepAnxietyConservative+1.
if (p1a3g eq 2) DAWBAsepAnxietyConservative = DAWBAsepAnxietyConservative+1.
if (p1a3i eq 2) DAWBAsepAnxietyConservative = DAWBAsepAnxietyConservative+1.
if (p1a3j eq 2) DAWBAsepAnxietyConservative = DAWBAsepAnxietyConservative+1.
if (p1a3k eq 2) DAWBAsepAnxietyConservative = DAWBAsepAnxietyConservative+1.
fre var DAWBAsepAnxietyConservative.

```

RECODE DAWBAsepAnxietyConservative (99=SYSMIS) (ELSE=COPY).
EXECUTE.

IF (p1a2 = 0 & p1emotion < 4) DAWBAsepAnxietyConservative =0.
EXECUTE.

if (mis_sep eq 1) DAWBAsepAnxietyConservative = 99.
mis val DAWBAsepAnxietyConservative (99).

IF (DAWBAsepAnxietyConservative >= 3) DAWBAsepAnxietyConservativeSymp=1.
EXECUTE.

IF (DAWBAsepAnxietyConservative < 3) DAWBAsepAnxietyConservativeSymp=0.
EXECUTE.

if (mis_sep eq 1) DAWBAsepAnxietyConservativeSymp = 99.
mis val DAWBAsepAnxietyConservativeSymp (99).

RECODE DAWBAsepAnxietyConservativeSymp (99=SYSMIS) (ELSE=COPY).
EXECUTE.

*B) The worries about separation have been present for at least 4 weeks

IF (p1a4 = 1) DAWBA4weeks = 1.
EXECUTE.

IF (p1a4 = 0) DAWBA4weeks = 0.
EXECUTE.

if (mis_sep eq 1) DAWBA4weeks = 99.
mis val DAWBA4weeks(99).
execute.

*C) Presence of clinically significant distress/ impairment

```
compute sepImpactCon=0.
if (p1a6 >=3) sepImpactCon = sepImpactCon+1.
if (p1a7a >=3) sepImpactCon = sepImpactCon+1.
if (p1a7b >= 3) sepImpactCon = sepImpactCon+1.
if (p1a7c >= 3) sepImpactCon = sepImpactCon+1.
if (p1a7d >= 3) sepImpactCon = sepImpactCon+1.
if (mis_sep eq 1) sepImpactCon = 99.
mis val sepImpactCon(99).
execute.
```

```
IF (sepImpactCon >= 1) sepImpactConScore = 1.
EXECUTE.
IF (sepImpactCon < 1) sepImpactConScore = 0.
EXECUTE.
if (mis_sep eq 1) sepImpactConScore = 99.
mis val sepImpactConScore(99).
execute.
```

fre var sepImpactConScore.

*FOR DIAGNOSIS, the presence of A, B, and C is required.

```
COMPUTE sepConDiagTotal=0.
if (DAWBAssepAnxietyConservativeSymp = 1) sepConDiagTotal = sepConDiagTotal+1.
if (DAWBA4weeks = 1) sepConDiagTotal = sepConDiagTotal+1.
if (sepImpactConScore = 1) sepConDiagTotal = sepConDiagTotal+1.
EXECUTE.
if (mis_sep eq 1) sepConDiagTotal = 99.
mis val sepConDiagTotal(99).
execute.
```

```
compute sepConDiag = 0.
IF (sepConDiagTotal = 3) sepConDiag = 1.
IF (sepConDiagTotal < 3) sepConDiag =0.
execute.
IF(mis_sep eq 1) sepConDiag = 99.
mis val sepConDiag (99).
execute.
```

** Separation anxiety - symptom score

compute sepSymptomScore = DAWBAssepAnxietyConservative.

```
execute.  
if (mis_sep eq 1) sepSymptomScore = 99.  
mis val sepSymptomScore (99).  
execute.
```