

ORCA - Online Research @ Cardiff

This is an Open Access document downloaded from ORCA, Cardiff University's institutional repository:https://orca.cardiff.ac.uk/id/eprint/131002/

This is the author's version of a work that was submitted to / accepted for publication.

Citation for final published version:

Mikhaylov, Roman, Wu, Fangda, Wang, Hanlin, Clayton, Aled , Sun, Chao, Xie, Zhihua , Liang, Dongfang, Dong, Yinhua, Yuan, Fan, Moschou, Despina, Wu, Zhenlin, Shen, Minghong, Yang, Jian , Fu, Yong Qing, Yang, Zhiyong , Burton, Christian, Errington, Rachel , Wiltshire, Marie and Yang, Xin 2020. Development and characterisation of acoustofluidic devices using detachable electrodes made from PCB. Lab on a Chip 20 (10) , pp. 1807-1814. 10.1039/C9LC01192G

Publishers page: http://dx.doi.org/10.1039/C9LC01192G

Please note:

Changes made as a result of publishing processes such as copy-editing, formatting and page numbers may not be reflected in this version. For the definitive version of this publication, please refer to the published source. You are advised to consult the publisher's version if you wish to cite this paper.

This version is being made available in accordance with publisher policies. See http://orca.cf.ac.uk/policies.html for usage policies. Copyright and moral rights for publications made available in ORCA are retained by the copyright holders.



Lab on a Chip



CORRECTION

View Article Online
View Journal | View Issue



Cite this: Lab Chip, 2020, 20, 3278

Correction: Development and characterisation of acoustofluidic devices using detachable electrodes made from PCB

Roman Mikhaylov,^a Fangda Wu,^a Hanlin Wang,^a Aled Clayton,^b Chao Sun,^c Zhihua Xie,^d Dongfang Liang,^e Yinhua Dong,^f Fan Yuan,^g Despina Moschou,^h Zhenlin Wu,ⁱ Ming Hong Shen,^j Jian Yang,^j Yongqing Fu,^k Zhiyong Yang,^l Christian Burton,^{ab} Rachel J. Errington,^b Marie Wiltshire^b and Xin Yang^a

DOI: 10.1039/d0lc90070b

rsc.li/loc

Correction for 'Development and characterisation of acoustofluidic devices using detachable electrodes made from PCB' by Roman Mikhaylov et al., Lab Chip, 2020, 20, 1807–1814, DOI: 10.1039/C9LC01192G.

The authors regret that the microfluidic channel dimensions in the "PCB-SAW fabrication and experimental setup" section of the original manuscript were incorrect. The correct microfluidic channel dimensions are 15 mm \times 200 μ m \times 60 μ m for length, width and height, respectively.

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.

^a Department of Electrical and Electronic Engineering, School of Engineering, Cardiff University, Cardiff CF24 3AA, UK

^b Tissue Micro-Environment Group, Division of Cancer & Genetics, School of Medicine, Cardiff University, Cardiff CF14 4XN, UK

^c School of Life Sciences, Northwestern Polytechnical University, 710129, P.R. China

^d Department of Civil Engineering, School of Engineering, Cardiff University, Cardiff CF24 3AA, UK

^e Department of Engineering, University of Cambridge, Cambridge CB2 1PZ, UK

f Department of Neurology, Tianjin 4th Centre Hospital Affiliated to Nankai University, 300140, P.R. China

g Department of Biomedical Engineering, School of Engineering, Duke University, NC 27708-0281, USA

^h Centre for Biosensors, Bioelectronics and Biodevices (C3Bio) and Department of Electronic & Electrical Engineering, University of Bath, Bath BA2 7AY, UK

ⁱ School of Optoelectronic Engineering and Instrumentation Science, Dalian University of Technology, 116023, P.R. China

^j Preclinical Studies of Renal Tumours Group, Division of Cancer and Genetics, School of Medicine, Cardiff University, Cardiff CF14 4XN, UK

^k Faculty of Engineering and Environment, Northumbria University, Newcastle Upon Tyne, Newcastle NE1 8ST, UK

¹School of Mechanical Engineering, Tianjin University, 300072, P.R. China